

This procedure for “Toyota Aurion, TRD, Avalon, Solara, Sienna, Prodigy, Sportivo, Presara, Touring remote key – Worn out button replacement procedure” was prepared by Polmex, Western Australian innovative Engineering Company, specializing in design and manufacture of special purpose Silicone products. Supplying to the market Silicone Buttons for worn out remote keys of various makes and models: Hyundai, Holden, Commodore, Ford, Mitsubishi, Nissan, Rover, Land Rover, Peugeot, BMW, Jeep, Mazda, Rover, Kia, Jeep, Mercedes and more...

For Orders please visit us on line at www.polmex.com.au

Polmex replacement Buttons/Pads are made from LSR Silicone and will not break, due to deteriorating effects of sunlight, water and chemicals commonly encountered in service such as Detergent, Oil, and Methanol. **Our silicone buttons are flexible and will not deform, change shape, degrade and break over period of time.**



Button Replacement Procedure

1. Prise open your remote with small screwdriver to end up with 2 parts: One consisting of hard shell and second one with electronic component and rubber key button pad.
2. Remove internal components and separate old rubber pad from electronic board. Do not remove battery. You can discard unusable, worn rubber pad.
3. To fit new Silicone pad in your remote, press it in the correct button cut outs. Press Silicone pad in till buttons are correctly positioned in respective holes of the plastic shell.
4. Next place electronic board inside of fitted in silicone pad. Place bottom part of the shell over the top part and press it till it closes firmly.

Once button replacement is finished, remote will work straight away with **no need for re-programming.**